



VALVE & TUBE TECHNICAL MARKINGS

Issue Date: 03.12.2009
Revised: 00.00.0000

(Imperial Example) Valve Model: BE4/3 PF90-513T

(Metric Example) Valve Model: BE100/80 PF6-513T

BE	4/3	PF	90	-	5	1	3	T
BE	100/80	PF	6	-	5	1	3	T
Body Type	Valve ID (DN)	Actuator Type	Operating Pressure		Flange Drilling	Body Material	Face-to-Face Standard	Accessories
BE = Body Enclosed BS = Body Sealed BO = Body Open	1 - 60 (inches) 25 - 1500 (mm) <u>Reduced Port</u> (Inlet / Outlet)	<u>A = Air Actuated (aiRFlex)</u> <i>with:</i> Positioner F = ElectroPneumatic D = Pneumatic <u>E = Electro-mechanic Actuator</u> <i>with:</i> F = Electric Positioner <u>H = Hydraulic Actuator</u> <i>with:</i> M = Manual Pump G = Motor Gear <u>M = Manual Handwheel</u> <i>with:</i> G = Gear Reducer L = Lock Out <u>P = Pneumatic Actuator</u> <i>with:</i> M = Manual Override Positioner F = ElectroPneumatic D = Pneumatic <u>Air Spring</u> RO = Fail Open RC = Fail Close <u>Mechanical Spring</u> KO = Fail Open KC = Fail Close	15 = 15psi 50 = 50psi 90 = 90psi 150 = 150psi 300 = 300psi 1 = 1bar 4 = 4bar 6 = 6bar 10 = 10bar 20 = 20bar 40 = 40bar		1 = DIN PN10 2 = DIN PN16 3 = DIN PN25 4 = DIN PN40 5 = ANSI 150# 6 = ANSI 300# 7 = ANSI 600# 8 = JIS 10 9 = AS2129 (Table D/E) 0 = Other	1 = Cast Iron 2 = Welded Carbon Steel 3 = Stainless Steel (AISI 316) 4 = Aluminum 5 = Ductile Cast Iron 9 = Other	1 = DIN 3202 F5 2 = DIN 3202 F15 3 = ASME B-16 (Short) 4 = ASME B-16 (Long) 5 = ISO 5752 (Table 6) 9 = No Standard	A = Manual Air Valve Switch C = MONSYS Box G = Gauges L = Proximity Limit Switches N = Mechanical Limit Switches Y = Magnetic Limit Switches P = Pressure Switch Q = Quick Exhaust Valves R = Filter/Regulator S = Solenoid T = Opening Tags V = Vacuum Pump X = Special Requirements

(Imperial Example) Tube Model: PGR4/3-150-3CST

(Metric Example) Tube Model: PGR100/80-10-3CST

PGR	4/3	-	150	-	3	CST
PGR	100/80	-	10	-	3	CST
Tube Material	Tube ID (DN)		Pressure Rating		Face-to-Face Standard	Accessories
CR = Chloroprene Rubber (Neoprene®) CSM = Chloro-Sulfonated Polyethylene Rubber (Hypalon®) EPDM = Ethylene-Propylene Rubber (Nordel®) FPM = Fluoro-Carbon Rubber (Viton®) HNBR = Hydrogenated Nitrile Rubber IIR = Chloro-Butyl Rubber NBR = Nitrile Rubber (Buna-N®) NR = Natural Rubber PGR = Pure Gum Rubber SBR = Styrene Butadiene Rubber <i>with</i> HT = High Temperature Rated FB = Foodgrade Black FW = Foodgrade White	1 - 60 (inches) 25 - 1500 (mm) <u>Reduced Port</u> (Inlet / Outlet)		15 = 15psi 50 = 50psi 90 = 90psi 150 = 150psi 300 = 300psi 600 = 600psi 1 = 1bar 4 = 4bar 6 = 6bar 10 = 10bar 20 = 20bar 40 = 40bar		1 = DIN 3202 F5 2 = DIN 3202 F15 3 = ASME B-16 (Short) 4 = ASME B-16 (Long) 5 = ISO 5752 (Table 6) 9 = No Standard	A = aiRFlex design C = Wear Sensor Wire T = Opening Tags S = Single Cone (reduced port) D = Double Cone (reduced port) Z = Straight Interior (filled arches) F = Full Flanges X = Special Requirements