



## VALVE & TUBE TECHNICAL MARKINGS

Issue Date: 8.5.2011  
Revised: 00.00.0000

(Imperial Example) Valve Model: RF-SKGF6 P90-53 SL / E

(Metric Example) Valve Model: RF-SKGF150 P6-53SL / E

RF-SKGF RF-SKGW	6 150	P P	90 - 6 -	5 5	3 3	- SL SL	/ E / E
Body Type	Valve ID (DN)	Actuator Type	Operating Pressure	Flange Drilling	Body Material	Accessories	Sleeve
F= Flanged W= Wafer INS = Insamcor	3- 24 (inches) 80 - 600 (mm)	<u>E = Electro-mechanic Actuator</u> <i>with:</i> F = Electric Positioner <u>H = Hydraulic Actuator</u> <i>with:</i> M = Manual Pump G = Motor Gear <u>M = Manual Handwheel</u> <i>with:</i> G = Gear Reducer L = Lock Out <u>P = Pneumatic Actuator</u> <i>with:</i> M = Manual Override <i>with:</i> L = Lock-Out <u>Positioner</u> F = ElectroPneumatic D = Pneumatic <u>Air Spring</u> RO = Fail Open RC = Fail Close <u>Mechanical Spring</u> KO = Fail Open KC = Fail Close	15 = 15psi 50 = 50psi 90 = 90psi 150 = 150psi 300 = 300psi 1 = 1bar 4 = 4bar 6 = 6bar 10 = 10bar 16 = 16bar 25 = 25bar 40 = 40bar	1 = DIN PN10 2 = DIN PN16 3 = DIN PN25 4 = DIN PN40 5 = ANSI 150# 6 = ANSI 300# 7 = ANSI 600# 8 = JIS 10 9 = AS2129 (Table D/E) 0 = Other	3 = Stainless Steel (AISI 316) 5 = Ductile Iron 9 = Other	G = Gauges L = Prox Limit Switches N = Mech Limit Switches Y = Reed Limit Switches R = Filter/Regulator S = Solenoid C = Residue Chamber X = Special Requirements A = Alloy 20 Blade F = SS904L Blade T = Titanium Grade Blade H = Hastelloy C Blade	E=EPDM V=Viton B=Butyl N=Neoprene

